

AN 1992:107871 CAPLUS
 DN 116:107871
 ED Entered STN: 20 Mar 1992
 TI Heat-resistant hot-melt **adhesives** based on ethylene copolymers
 IN Eastman, Ernest Francis; Statz, Robert Joseph
 PA du Pont de Nemours, E. I., and Co., USA
 SO PCT Int. Appl., 28 pp.
 CODEN: PIXXD2
 DT Patent
 LA English
 IC ICM C08J005-12
 CC 38-3 (Plastics Fabrication and Uses)
 FAN.CNT 1

	PATENT NO.	KIND	DATE	APPLICATION NO.	DATE
PI	WO 9118043	A1	19911128	WO 1991-US2840	19910501
	W: CA				
	RW: AT, BE, CH, DE, DK, ES, FR, GB, GR, IT, LU, NL, SE				
	JP 04227982	A2	19920818	JP 1991-113147	19910517
PRAI	US 1990-525378		19900517		
	US 1991-670914		19910313		

AB The title **adhesives**, useful for bonding metals, plastics, wood, and paper, comprise C₂H₄ copolymers with 10-50% C₁-8-alkyl acrylate or C₁-8-alkyl vinyl ether and 3-30 CO or SO₂, 5-80 compatible tackifier, and, optionally, plasticizers and waxes. Thus, an **adhesive** contg. 16.5:51.6:31.9 CO-C₂H₄-Et acrylate copolymer 40, tackifier 60, and antioxidant 1 part had viscosity after 0 and 3 h at 176.degree. 105 and 102.5 P; vs. 157 and 1000, resp., for CO-C₂H₄-vinyl acetate copolymer.

ST ethylene copolymer **adhesive**; acrylate copolymer **adhesive**; vinyl ether copolymer **adhesive**; carbon monoxide copolymer **adhesive**; sulfur dioxide copolymer **adhesive**; **adhesive** hot melt ethylene copolymer

IT **Adhesives**
 (hot-melt, ethylene copolymers, with stable melt viscosity)

IT 41500-28-1 61843-70-7 **62975-63-7** 73764-12-2 112242-66-7
 RL: TEM (Technical or engineered material use); USES (Uses)
 (**adhesives**, hot-melt, with stable melt viscosity)